

AL2200 - 110126

Indicates target Ride Height for this tabulation

Drawing number	Ride Height	8000	10000	12000	14000	16000	17000	18000	19000	20000	22000	23000	24000	25000	Output at Ground
		PSI required to achieve Output at Ground													
110126-1	9.50	27	36	45	54	63	67	72	76	80	89	94	98	102	
	10.50	28	37	46	55	63	68	72	77	81	90	95	99	104	
	11.50	29	38	48	57	66	71	75	80	85	94	99	103	108	
110126-3	11.50	27	36	44	53	62	66	71	75	79	88	92	97	101	
	12.50	27	36	45	54	63	67	72	76	80	89	94	98	103	
	13.50	29	39	48	58	67	72	77	81	86	95	100	105	110	
110126-5	13.50	27	35	44	53	61	66	70	74	79	87	92	96	100	
	14.50	27	35	44	53	61	65	70	74	78	87	91	96	100	
	15.50	29	38	47	56	65	70	75	79	84	93	98	102	107	

Some capacities shown may not be best suited for the suspension based on too much brake force for the applied load. Therefore, braking capacity may have to be downsized to accommodate.

Pressure requirements are approximations and will need to be calibrated on a weigh scale capable of handling the Output at Ground forces in the above chart. Weight of the axle, hubs and drums based on 445/65R22.5 tires, steel wheels, and Cast Hubs and Drums ----- 1800