



# TRAILER ORDERING GUIDE

If additional options are required and do not appear on this guide, please note when ordering. This sheet covers basic information.

TO: \_\_\_\_\_ FROM: \_\_\_\_\_

COMPANY NAME: \_\_\_\_\_

DATE: \_\_\_\_\_ PHONE: \_\_\_\_\_ FAX: \_\_\_\_\_

## SUSPENSION

(Check all that apply)

**SUSPENSION MODEL:** TA  TI

**CAPACITY:** 25K  30K

**RIDE HEIGHT:**  
TOP MOUNT (14 THRU 19) Ride Height: \_\_\_\_\_  
LOW MOUNT (9 THRU 12) Ride Height: \_\_\_\_\_  
UNDERSLUNG (6.5 THRU 9) Ride Height: \_\_\_\_\_  
YOKE MOUNT (5.5 THRU 9) Ride Height: \_\_\_\_\_

**FRAME BRACKET:** Bolt-On  Weld-On  Wing   
**Mounting bolt size:** 0.500"  Other  \_\_\_\_\_

**STRAPS:** Yes  No  Strap over shock: Yes  No

**BEAM CENTERS:** 35" Centers  41" Centers  Other  \*Different options available upon request

**CHANNEL:** Standard C-Channel  Bolt-on C-Channel  Customer Supplied   
Gussets  Other  \_\_\_\_\_

**COLLAR:** Align-Trac  Welded  Eccentric

**LIFT KIT OPTION:** Yes  No

**COMMENTS** \_\_\_\_\_  
\_\_\_\_\_

## AXLES

(Check all that apply)

**AXLE TYPE:** Straight  6" Drop  6" Inverted Drop

**SPINDLE TYPE:** N Spindle  P Spindle

**AXLE TRACK:** 71.5"  77.5"  Other  \_\_\_\_\_

**WALL THICKNESS:** 5/8" Nominal  3/4"

**TIRE INFLATION:** TIREMAAX® CP  PSI  Other  \_\_\_\_\_

**BRAKE SIZE:** 12.25" x 7.5"  16.5" x 7"  16.5" x 8.625"

**BRAKE CHAMBER SIZE:** Service / Spring: 24/24  24/30  30/30   
Service Only Type 24  Service Only Type 30

**CAM SPLINES:** 28 Spline  Other  \_\_\_\_\_

**COMMENTS** \_\_\_\_\_  
\_\_\_\_\_

# TRAILER ORDERING GUIDE

Continued

## DRUM BRAKES

(Check all that apply)

<b>SLACK ADJUSTER:</b>	Yes <input type="checkbox"/>	No <input type="checkbox"/>		
<b>BRAKE S-CAM LENGTH:</b>	23.75" (Air Susp.) <input type="checkbox"/>	Bent Tube Axle (Uses special length) <input type="checkbox"/>		
	Other (17" min. - 27.75" max.) <input type="checkbox"/>			
<b>BRAKE S-CAM ENCLOSURE:</b>	None <input type="checkbox"/>	Cam Tube System <input type="checkbox"/>		
<b>BRAKE ROTATION / POSITION:</b>	BR1 CAMS REAR CHAMBERS DOWN <input type="checkbox"/>	BR2 CAMS FRONT CHAMBERS UP <input type="checkbox"/>		
<b>BRAKE DUST SHIELD:</b>	None <input type="checkbox"/>	Yes <input type="checkbox"/>		
<b>ABS TONE RING:</b>	Yes <input type="checkbox"/>	No <input type="checkbox"/>		
<b>ABS SENSORS INSTALLED:</b>	Yes <input type="checkbox"/>	No <input type="checkbox"/>		
<b>SPINDLE NUT SYSTEM:</b>	Standard <input type="checkbox"/>	Other <input type="checkbox"/> _____		
<b>HUB MOUNTED:</b>	Hub Pilot <input type="checkbox"/>	Stud Piloted <input type="checkbox"/>		
<b>HUB MATERIAL:</b>	Cast Iron <input type="checkbox"/>	Aluminum <input type="checkbox"/>	ADI <input type="checkbox"/>	
<b>DRUM TYPE:</b>	Cast Iron <input type="checkbox"/>	Other <input type="checkbox"/> _____		
<b>BOLT PATTERN:</b>	10 Hole 11.25" BC <input type="checkbox"/>	8 Hole 275mm 12.25" x 7.5" Brakes <input type="checkbox"/>		
<b>STUD LENGTH:</b>	Long <input type="checkbox"/>	Short <input type="checkbox"/>	Other <input type="checkbox"/> _____	
<b>LUBE TYPE:</b>	None <input type="checkbox"/>	Oil SAE 80/90 <input type="checkbox"/>	Semi-Fluid Grease <input type="checkbox"/>	
<b>HUBCAP TYPE:</b>	Standard <input type="checkbox"/>	Grease Type <input type="checkbox"/>	TIREMAAX® CP <input type="checkbox"/>	Other <input type="checkbox"/> _____
<b>COMMENTS</b>	_____			

Actual product performance may vary depending upon vehicle configuration, operation, service and other factors.  
All applications must comply with applicable specifications from Watson & Chalin and the respective vehicle manufacturer.  
Contact Watson & Chalin for additional details regarding specifications, applications, capacities, and operation, service and maintenance instructions.

Contact Watson & Chalin at 972.547.6020 for additional information.



**Watson & Chalin**  
725 E. University Drive, McKinney, Texas 75069  
972.547.6020 • 800.445.0736 • Fax 972.542.0097  
[www.wcsuspensions-intl.com](http://www.wcsuspensions-intl.com)

