



AIR DISC BRAKE ORDERING GUIDE

If additional options are required and do not appear on this guide, please note when ordering. This sheet covers basic information.

TO: _____ FROM: _____

COMPANY NAME: _____

DATE: _____ PHONE: _____ FAX: _____

(Check all that apply)

ADB PACKAGE:	WABCO PAN22-1		
ADB PAD / LINING:	WABCO 230		
BRAKE CHAMBER:	<input type="checkbox"/> Wabco 20/24 STD <input type="checkbox"/> Wabco 20 (Converter Dolly Applications)		
HUB TYPE:	Hub pilot, 10 stud, 11.25" BC		
DUAL / SUPER SINGLE:	<input type="checkbox"/> Dual (Long Stud)	<input type="checkbox"/> Super Single (Short Stud)	<input type="checkbox"/> Super Single (Long Stud)
ABS SENSORS (Required):	<input type="checkbox"/> Haldex (19.7" or 78.7")	<input type="checkbox"/> Bendix (14.84" or 78.7")	<input type="checkbox"/> Wabco (39.4")
DUST SHIELDS:	REQUIRED		
(RTR) READY-TO-ROLL® Wheel-End Package:	<input type="checkbox"/> Standard 1-year	<input type="checkbox"/> Hendrickson Extended-Life System™ - HXL3®, HXL5®	<input type="checkbox"/> ConMet Preset®
SPINDLE OPTIONS:	<input type="checkbox"/> HN <input type="checkbox"/> HP	<input type="checkbox"/> HN <input type="checkbox"/> HP	<input type="checkbox"/> HN <input type="checkbox"/> HP
HUB BRAND / MATERIAL:	<input type="checkbox"/> Hendrickson Ductile Iron	<input type="checkbox"/> Hendrickson Ductile Iron	<input type="checkbox"/> ConMet Preset® AL
ROTOR BRAND / MATERIAL:	<input type="checkbox"/> Hendrickson Cast Iron		<input type="checkbox"/> ConMet Cast Iron
ROTOR SIZE / STYLE:	<input type="checkbox"/> 430 mm / U-shaped	<input type="checkbox"/> 430 mm / U-shaped	<input type="checkbox"/> 430 mm / Flat
LUBE OPTIONS:	<input type="checkbox"/> SAE 80/90 <input type="checkbox"/> Synthetic 75W/90 <input type="checkbox"/> Semi-fluid grease	<input type="checkbox"/> SAE 80/90 <input type="checkbox"/> Synthetic 75W/90 <input type="checkbox"/> Semi-fluid grease	<input type="checkbox"/> Synthetic 75W/90 <input type="checkbox"/> Semi-fluid grease
HUB CAP: NON-TIREMAAX	<input type="checkbox"/> Standard: Stemco Bolt On <input type="checkbox"/> Dual Dynamics	<input type="checkbox"/> Hendrickson Aluminum Cast Hubcap	<input type="checkbox"/> Standard: Dual Dynamics <input type="checkbox"/> Option: Stemco Sentinel
TIREMAAX	<input type="checkbox"/> TIREMAAX® CP		
SEAL:	<input type="checkbox"/> Federal Mogul Gold Seal	<input type="checkbox"/> Federal Mogul Gold Seal	<input type="checkbox"/> Federal Mogul Gold Seal
SPINDLE NUT:	<input type="checkbox"/> Standard: 3-Piece Nut <input type="checkbox"/> Option: Stemco Pro-Torq	<input type="checkbox"/> PRECISION240® or PRECISION320®	<input type="checkbox"/> Standard: 3-Piece Nut <input type="checkbox"/> Option: Stemco Pro-Torq

COMMENTS _____

AIR DISC BRAKE ORDERING GUIDE

Continued

(Check all that apply)

ADB PACKAGE:	KNORR-BENDIX ADB22X					
ADB PAD / LINING:	JURID 539-29 / BX275					
BRAKE CHAMBER:	KNORR 18/24 STD					
HUB TYPE:	Hub pilot, 10 stud, 11.25" BC					
DUAL / SUPER SINGLE:	<input type="checkbox"/> Dual (Long Stud)	<input type="checkbox"/> Super Single (Short Stud)	<input type="checkbox"/> Super Single (Long Stud)			
ABS SENSORS (Required):	<input type="checkbox"/> Bendix (14.84" or 78.7")	<input type="checkbox"/> Haldex (19.7" or 78.7")	<input type="checkbox"/> Wabco (39.4")			
DUST SHIELDS:	REQUIRED					
(RTR) READY-TO-ROLL® Wheel-End Package:	<input type="checkbox"/> Standard 1-year	<input type="checkbox"/> Hendrickson Extended-Life System™ - HXL3®, HXL5®	<input type="checkbox"/> ConMet Preset®			
SPINDLE OPTIONS:	<input type="checkbox"/> HN <input type="checkbox"/> HP	<input type="checkbox"/> HN <input type="checkbox"/> HP	<input type="checkbox"/> HP	<input type="checkbox"/> HN or HP	<input type="checkbox"/> HN or HP	
HUB BRAND / MATERIAL:	<input type="checkbox"/> ConMet Ductile Iron	<input type="checkbox"/> ConMet Ductile Iron	<input type="checkbox"/> ConMet Preset Ductile Iron	<input type="checkbox"/> ConMet Preset AL	<input type="checkbox"/> ConMet Preset AL Splined	
ROTOR BRAND / MATERIAL:	<input type="checkbox"/> Knorr Ductile Iron	<input type="checkbox"/> Knorr Ductile Iron	<input type="checkbox"/> Knorr Cast Iron	<input type="checkbox"/> ConMet Cast Iron	<input type="checkbox"/> Knorr Cast Iron	
ROTOR SIZE / STYLE:	<input type="checkbox"/> 430 mm / U-shaped	<input type="checkbox"/> 430 mm / U-shaped	<input type="checkbox"/> 430 mm / U-shaped	<input type="checkbox"/> 430 mm / Flat	<input type="checkbox"/> 430 mm / Splined	
LUBE OPTIONS:	<input type="checkbox"/> SAE 80/90 <input type="checkbox"/> Synthetic 75W/90 <input type="checkbox"/> Semi-fluid grease	<input type="checkbox"/> SAE 80/90 <input type="checkbox"/> Synthetic 75W/90 <input type="checkbox"/> Semi-fluid grease	<input type="checkbox"/> Synthetic 75W/90 <input type="checkbox"/> Semi-fluid grease			
HUB CAP: NON-TIREMAAX®	<input type="checkbox"/> Standard: Stemco Bolt On <input type="checkbox"/> Option: Stemco Sentinel <input type="checkbox"/> Dual Dynamics	<input type="checkbox"/> Hendrickson Aluminum Cast Hubcap	<input type="checkbox"/> Standard: Dual Dynamics <input type="checkbox"/> Option: Stemco Sentinel			
	TIREMAAX	<input type="checkbox"/> TIREMAAX® CP				
SEAL:	<input type="checkbox"/> Federal Mogul Gold Seal	<input type="checkbox"/> Federal Mogul Gold Seal	<input type="checkbox"/> FM Gold Seal	<input type="checkbox"/> FM Gold Seal	<input type="checkbox"/> FM Gold Seal	
SPINDLE NUT:	<input type="checkbox"/> Standard: 3-Piece Nut <input type="checkbox"/> Option: Stemco Pro-Torq	<input type="checkbox"/> PRECISION240® or PRECISION320®	<input type="checkbox"/> Standard: 3-Piece Nut <input type="checkbox"/> Option: Stemco Pro-Torq			

COMMENTS _____

Actual product performance may vary depending upon vehicle configuration, operation, service and other factors.
All applications must comply with applicable specifications from Watson & Chalin and the respective vehicle manufacturer.
Contact Watson & Chalin for additional details regarding specifications, applications, capacities, and operation, service and maintenance instructions.

Contact Watson & Chalin at 972.547.6020 for additional information.



Watson & Chalin
725 E. University Drive, McKinney, Texas 75069
972.547.6020 • 800.445.0736 • Fax 972.542.0097
www.wcsuspensions-intl.com

