# LIFT AXLE QUICK REFERENCE


The information contained in this literature provides a quick glance of critical data and dimensions of our lift axles and suspension systems that will be helpful while going through the axle specification process. Additionally, most popular service kits are listed on the back page for a good reference on parts recommended to keep in stock.


## SL / AL QUICK REFERENCE (STANDARD MODELS)


MODEL	CAPACITY (LBS.)	WEIGHT (LBS.)	RIDE HEIGHT (IN.)	LIFT (IN.)	PACKAGE SPACE (IN.)	HUB FACE (IN.)	BRAKE SIZE	STUDS	WHEEL SIZE (IN.)
SL08	8,000	672	13 - 19	8	22.1	86	325 × 100 mm	6	17.5
SL10	10,000	719	13 - 19	8	22.1	89	325 × 100 mm	8	19.5
SL13	13,500	819	8 - 17	8	22.1	92	15 × 4 in., 16.5 × 5 in., Disc	10	22.5
SL20	20,000	1,297	8 - 13	8	26.5	89	16.5 × 6 in.	10	22.5
SL25	25,000	1,500	8 - 15	7	25	71.5 Track	16.5 × 7 in.	10	22.5
AL25	Up to 25,000	1,222	8 - 15	7	25	71.5 Track	16.5 × 6 in.	10	22.5

### **Ride Height Measurement Concept**

- A. Loaded Ground To Frame (GTF) Measurement
- B. Static Loaded Radius (SLR) of tire
- C. Ride Height (A B = C)











For more information, call 800.445.0736

## **LIFT AXLE** QUICK REFERENCE

KINGPIN KITS				
SL08	SL085x and SL089x –	Meritor – Kaiser Qwik Kit – K941R (W&C number 19082)		
		Westport – SRK115 (without kingpins – SRK115-01); No Kaiser Qwik Kit Available		
SL10	SL10-1093 –	[H] Kit R-010300; No Kaiser Qwik Kit Available		
SL13	SL1186 / SL1187 / SL1188 / SL1190 –			
		Meritor – SRK102 (without kingpins – SRK102-01); Kaiser Qwik Kit - K961L (W&C number 19081)		
		Westport – SRK112 (without kingpins – SRK112-01); Kaiser Qwik Kit - K130W (W&C number K130W)		
	SL1195 / SL13AA –	[H] Kit R-010300; No Kaiser Qwik Kit Available		
SL20	SL2089 / SL2055 –	Meritor – SRK105 (without kingpins SRK105-01); Kaiser Qwik Kit - KH931L (W&C number 19080)		
		Westport – SRK120 (without kingpins – SRK120-01); Kaiser Qwik Kit - K181R (Not verified by W&C, no W&C part number)		
	SL2065 –	[H] Kit R-010300; No Kaiser Qwik Kit Available		
	SL2200 -	If KGI Axle, KGI Kit Number 10630		
	JL2200	II NOI PAIC, NOI NIL HUIIIDEI 10030		

1	RAILING	ARM BUSHING KITS				
<b>SL08</b> SL085x –		SRK16 (Hardware only – SRK16-01)				
	SL089x -	SRK1190-1				
SL10	SL1093 -	SRK1190-1				
SL13	SL1100 -	SRK08 (Hardware only SRK08-01)				
	SL1186 / SL1187 / SL1188 –					
		SRK14 (Hardware only SRK14-01)				
	SL119x –	SRK1190-1 (Hardware only SRK1190-2)				
	SL13AA –	SRKSL13AA-1 (Hardware only SRKSL13AA-2)				
	SL1193THL –	SL1193THL				
SL20	SL1800 -	SRK12				
	SL2089 –	SRK2089-1				
	SL2055 -	SRK2055-2				
	SL2065 -	SRK2055-2				
SL25	AL / SL2200 –					
	Pivot – SRK01 (Hardware only SRK01-01)					
	Axle Seat – SRK02 (Hardware only SRK02-01)					

LOAD AIR SPRING					
SL08 / SL10 / SL13 (All except SL1100) — AS0048 (Daimler and PACCAR units use AS0048-3C)					
	SL1100 -	AS0019			
SL20	SL1800 –	AS0006			
	SL2089 –	AS0047G			
	SL2055 –	AS0222			
	SL2065 –	AS0222			
SL25	AL / SL2200 —	AS0057			

LIFT AIR SPRING			
SL085x –	AS0068		
SL089x –	AS0058C		
3	AS0058C		
SL1800 –	AS0058-1F		
SL2089 –	AS0058-1F		
SL2055 –	AS0058-1F		
SL2065 –	AS0058-1F		
AL / SL2200 —	AS0058C		
	SL085x - SL089x - 3 SL1800 - SL2089 - SL2055 - SL2065 -	SL085x –       AS0068         SL089x –       AS0058C         3       AS0058C         SL1800 –       AS0058-1F         SL2089 –       AS0058-1F         SL2055 –       AS0058-1F         SL2065 –       AS0058-1F	

Actual product performance may vary depending upon vehicle configuration, operation, service and other factors.

All applications must comply with applicable specifications from W&C and the respective vehicle manufacturer.

Contact W&C for additional details regarding specifications, applications, capacities, and operation, service and maintenance instructions.

#### Contact W&C at 972.547.6020 for additional information.



#### W&C

725 E. University Drive, McKinney, Texas 75069 972.547.6020 • 800.445.0736 • Fax 972.542.0097

www.wcsuspensions-intl.com

