



# AIR DISC BRAKE ORDERING GUIDE

If additional options are required and do not appear on this guide, please note when ordering. This sheet covers basic information.

TO: \_\_\_\_\_ FROM: \_\_\_\_\_

COMPANY NAME: \_\_\_\_\_

DATE: \_\_\_\_\_ PHONE: \_\_\_\_\_ FAX: \_\_\_\_\_

(Check all that apply)

<b>ADB PACKAGE:</b>	<b>WABCO PAN22-1</b>		
<b>ADB PAD / LINING:</b>	<b>WABCO 230</b>		
<b>BRAKE CHAMBER:</b>	<input type="checkbox"/> Wabco 20/24 STD <input type="checkbox"/> Wabco 20 (Converter Dolly Applications)		
<b>HUB TYPE:</b>	Hub pilot, 10 stud, 11.25" BC		
<b>DUAL / SUPER SINGLE:</b>	<input type="checkbox"/> Dual (Long Stud)	<input type="checkbox"/> Super Single (Short Stud)	<input type="checkbox"/> Super Single (Long Stud)
<b>ABS SENSORS (Required):</b>	<input type="checkbox"/> Haldex (19.7" or 78.7")	<input type="checkbox"/> Bendix (14.84" or 78.7")	<input type="checkbox"/> Wabco (39.4")
<b>DUST SHIELDS:</b>	<b>REQUIRED</b>		
<b>(RTR) READY-TO-ROLL® Wheel-End Package:</b>	<input type="checkbox"/> Standard 1-year	<input type="checkbox"/> Hendrickson Extended-Life System™ - HXL3®, HXL5®	<input type="checkbox"/> ConMet Preset®
<b>SPINDLE OPTIONS:</b>	<input type="checkbox"/> HN <input type="checkbox"/> HP	<input type="checkbox"/> HN <input type="checkbox"/> HP	<input type="checkbox"/> HN <input type="checkbox"/> HP
<b>HUB BRAND / MATERIAL:</b>	<input type="checkbox"/> Hendrickson Ductile Iron	<input type="checkbox"/> Hendrickson Ductile Iron	<input type="checkbox"/> ConMet Preset® AL
<b>ROTOR BRAND / MATERIAL:</b>	<input type="checkbox"/> Hendrickson Cast Iron		<input type="checkbox"/> ConMet Cast Iron
<b>ROTOR SIZE / STYLE:</b>	<input type="checkbox"/> 430 mm / U-shaped	<input type="checkbox"/> 430 mm / U-shaped	<input type="checkbox"/> 430 mm / Flat
<b>LUBE OPTIONS:</b>	<input type="checkbox"/> SAE 80/90 <input type="checkbox"/> Synthetic 75W/90 <input type="checkbox"/> Semi-fluid grease	<input type="checkbox"/> SAE 80/90 <input type="checkbox"/> Synthetic 75W/90 <input type="checkbox"/> Semi-fluid grease	<input type="checkbox"/> Synthetic 75W/90 <input type="checkbox"/> Semi-fluid grease
<b>HUB CAP: NON-TIREMAAX</b>	<input type="checkbox"/> Standard: Stemco Bolt On <input type="checkbox"/> Dual Dynamics	<input type="checkbox"/> Hendrickson Aluminum Cast Hubcap	<input type="checkbox"/> Standard: Dual Dynamics <input type="checkbox"/> Option: Stemco Sentinel
<b>TIREMAAX</b>	<input type="checkbox"/> TIREMAAX® CP		
<b>SEAL:</b>	<input type="checkbox"/> Federal Mogul Gold Seal	<input type="checkbox"/> Federal Mogul Gold Seal	<input type="checkbox"/> Federal Mogul Gold Seal
<b>SPINDLE NUT:</b>	<input type="checkbox"/> Standard: 3-Piece Nut <input type="checkbox"/> Option: Stemco Pro-Torq	<input type="checkbox"/> PRECISION240® or PRECISION320®	<input type="checkbox"/> Standard: 3-Piece Nut <input type="checkbox"/> Option: Stemco Pro-Torq

COMMENTS \_\_\_\_\_

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

# AIR DISC BRAKE ORDERING GUIDE

Continued

(Check all that apply)

<b>ADB PACKAGE:</b>	<b>KNORR-BENDIX ADB22X</b>					
<b>ADB PAD / LINING:</b>	<b>JURID 539-29 / BX275</b>					
<b>BRAKE CHAMBER:</b>	<b>KNORR 18/24 STD</b>					
<b>HUB TYPE:</b>	Hub pilot, 10 stud, 11.25" BC					
<b>DUAL / SUPER SINGLE:</b>	<input type="checkbox"/> Dual (Long Stud)	<input type="checkbox"/> Super Single (Short Stud)	<input type="checkbox"/> Super Single (Long Stud)			
<b>ABS SENSORS (Required):</b>	<input type="checkbox"/> Bendix (14.84" or 78.7")	<input type="checkbox"/> Haldex (19.7" or 78.7")	<input type="checkbox"/> Wabco (39.4")			
<b>DUST SHIELDS:</b>	<b>REQUIRED</b>					
<b>(RTR) READY-TO-ROLL® Wheel-End Package:</b>	<input type="checkbox"/> Standard 1-year	<input type="checkbox"/> Hendrickson Extended-Life System™ - HXL3®, HXL5®	<input type="checkbox"/> ConMet Preset®			
<b>SPINDLE OPTIONS:</b>	<input type="checkbox"/> HN <input type="checkbox"/> HP	<input type="checkbox"/> HN <input type="checkbox"/> HP	<input type="checkbox"/> HP	<input type="checkbox"/> HN or HP	<input type="checkbox"/> HN or HP	
<b>HUB BRAND / MATERIAL:</b>	<input type="checkbox"/> ConMet Ductile Iron	<input type="checkbox"/> ConMet Ductile Iron	<input type="checkbox"/> ConMet Preset Ductile Iron	<input type="checkbox"/> ConMet Preset AL	<input type="checkbox"/> ConMet Preset AL Splined	
<b>ROTOR BRAND / MATERIAL:</b>	<input type="checkbox"/> Knorr Ductile Iron	<input type="checkbox"/> Knorr Ductile Iron	<input type="checkbox"/> Knorr Cast Iron	<input type="checkbox"/> ConMet Cast Iron	<input type="checkbox"/> Knorr Cast Iron	
<b>ROTOR SIZE / STYLE:</b>	<input type="checkbox"/> 430 mm / U-shaped	<input type="checkbox"/> 430 mm / U-shaped	<input type="checkbox"/> 430 mm / U-shaped	<input type="checkbox"/> 430 mm / Flat	<input type="checkbox"/> 430 mm / Splined	
<b>LUBE OPTIONS:</b>	<input type="checkbox"/> SAE 80/90 <input type="checkbox"/> Synthetic 75W/90 <input type="checkbox"/> Semi-fluid grease	<input type="checkbox"/> SAE 80/90 <input type="checkbox"/> Synthetic 75W/90 <input type="checkbox"/> Semi-fluid grease	<input type="checkbox"/> Synthetic 75W/90 <input type="checkbox"/> Semi-fluid grease			
<b>HUB CAP: NON-TIREMAAX®</b>	<input type="checkbox"/> Standard: Stemco Bolt On <input type="checkbox"/> Option: Stemco Sentinel <input type="checkbox"/> Dual Dynamics	<input type="checkbox"/> Hendrickson Aluminum Cast Hubcap	<input type="checkbox"/> Standard: Dual Dynamics <input type="checkbox"/> Option: Stemco Sentinel			
	<b>TIREMAAX</b>		<input type="checkbox"/> TIREMAAX® CP			
<b>SEAL:</b>	<input type="checkbox"/> Federal Mogul Gold Seal	<input type="checkbox"/> Federal Mogul Gold Seal	<input type="checkbox"/> FM Gold Seal	<input type="checkbox"/> FM Gold Seal	<input type="checkbox"/> FM Gold Seal	
<b>SPINDLE NUT:</b>	<input type="checkbox"/> Standard: 3-Piece Nut <input type="checkbox"/> Option: Stemco Pro-Torq	<input type="checkbox"/> PRECISION240® or PRECISION320®	<input type="checkbox"/> Standard: 3-Piece Nut <input type="checkbox"/> Option: Stemco Pro-Torq			

**COMMENTS** \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

Actual product performance may vary depending upon vehicle configuration, operation, service and other factors.  
All applications must comply with applicable specifications from Watson & Chalin and the respective vehicle manufacturer.  
Contact Watson & Chalin for additional details regarding specifications, applications, capacities, and operation, service and maintenance instructions.

Contact Watson & Chalin at 972.547.6020 for additional information.



**Watson & Chalin**  
725 E. University Drive, McKinney, Texas 75069  
972.547.6020 • 800.445.0736 • Fax 972.542.0097  
[www.wcsuspensions-intl.com](http://www.wcsuspensions-intl.com)

